



BlackDiamond® Primer Resin

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)
Date of issue: 03/24/2016 Revision date: 04/19/2017 Supersedes: 03/24/2016

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : BlackDiamond® Primer Resin
Product ID : BlackDiamond® Primer Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Epoxy coating and reinforcement for pipe repair
Use advised against : None identified

1.3. Details of the supplier of the safety data sheet

Manufacturer:
Clock Spring Company
621 Lockhaven Drive
Houston, TX 77073

Tel: 1-281-590-849

1.4. Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Skin corrosion/irritation, Category2
Eye damage/irritation, Category 2
Sensitization - Skin, Category1B
Specific target organ toxicity (Single Exposure) [Respiratory tract irritation] , Category 3

2.2. Label elements

Labelling

Hazard pictograms :



Signal word :

Warning

Hazard statements :

Causes skin irritation
May cause an allergic skin reaction
Causes serious eye irritation
May cause respiratory irritation

Precautionary statements :

Avoid breathing mist, vapors, spray
Wash face, hands thoroughly after handling
Contaminated work clothing must not be allowed out of the workplace
Wear protective gloves
If on skin: Wash with plenty of water
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If skin irritation occurs: Get medical advice/attention
If skin irritation or rash occurs: Get medical advice/attention
If eye irritation persists: get medical advice/attention
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Use only outdoors or in a well-ventilated area
Take off contaminated clothing and wash it before reuse
Wash contaminated clothing before reuse
Store in a well-ventilated place. Keep container tightly closed

BlackDiamond® Primer Resin

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

Other hazards which do not result in classification : Spills of this product present a serious slipping hazard.

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixture

Name	Product identifier	%
phenol,4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane	(CAS No) 25068-38-6	80 - 90
Proprietary Resin	(CAS No) Confidential	5 - 8
Phenol, polymer with formaldehyde, glycidyl ether	(CAS No) 28064-14-4	3 - 5

Some constituent(s) and/or exact percentage(s) are being withheld as trade secrets.

There are no additional ingredients, which in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Any occupational exposure limits, if available, are provided in section 8 of this SDS.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention.
- First-aid measures after skin contact : Rinse skin with plenty of water. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for 15-20 minutes. Continue washing with soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before re-use.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for several minutes, while holding the eyelids open. If eye irritation persists: get medical advice/attention.
- First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison center immediately if large quantities have been ingested or inhaled. If it is suspected that fumes are still presented, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing breathing mouth to mouth resuscitation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use fire-extinguishing media appropriate for surrounding materials. Foam. Dry powder. Carbon dioxide. Water spray. Sand. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No additional information available.
- Explosion hazard : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous thermal decomposition products : Thermal decomposition products may contain carbon monoxide, carbon dioxide, halogenated compounds.

BlackDiamond® Primer Resin

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Isolate immediate hazard area and keep unauthorized personnel out. Stop leak if safe to do so. Special danger of slipping by leaking/spilling product. Avoid contact with eyes and skin. Avoid breathing mist and vapors.

6.1.1. For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Avoid breathing mist or vapors.

6.1.2. For emergency responders

Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in section 8 of suitable and unsuitable materials.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid disposal of spilled material and runoff and contact with soil, waterways, drains and sewers.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Small spill: Stop leak if possible without risk. Move containers from spill area. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect all waste in suitable and labelled containers and dispose according to local legislation. Store away from other materials. Ensure all national/local regulations are observed.
- Large spill: Stop leak if possible without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, watercourses, basements or confined areas.

6.4. Reference to other sections

refer to section 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Read label before use. Obtain special instructions before use. Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing mist, vapors and spray. Wear personal protective equipment. Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool well-ventilated place. Keep container tightly closed when not in use. Keep away from incompatible materials. Keep away from sources of heat and protect from physical damage. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.
- Incompatible materials : Strong oxidizing agents. Strong acids. Aliphatic amines.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

BlackDiamond® Primer Resin

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Use only with adequate ventilation. Local exhaust or ventilation or other engineering controls must be provided to keep worker exposure to airborne containment below recommended levels. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

Personal protective equipment : Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection : Wear gloves. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves.

Suitability and durability of gloves are dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, and dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.

Eye protection : Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for the entire face, use in combination with a face shield.

Skin and body protection : Use of an apron and boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization.

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect the worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Other information : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous liquid
Color	: Light yellow
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ca 400 °F
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Density	: ca 1.17 (water=1)
Solubility	: Negligible
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity	: No data available
Explosive properties	: No data available

BlackDiamond® Primer Resin

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Oxidising properties : No data available

Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage condition

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Aliphatic amines.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

React with significant heat release with some curing agents. Some cure reaction may drive char and decompose the resin system, generating unidentified fumes, and vapors, which may be toxic. Heating this substance above 300 °F in the presence of air may cause slow oxidative decomposition. Above 500 °F polymerization may occur.

Some combination of resin and curing agent can produce the exothermic reaction, which in large masses can cause runaway polymerization and charring of the reactants.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
(Based on available data, the classification criteria are not met)

Skin corrosion/irritation : Causes skin irritation.
No test data available. Irritation properties are evaluated according to the criteria of the third revision of the GHS.

Serious eye damage/irritation : Causes serious eye irritation.
No test data available. Irritation properties are evaluated according to the criteria of the third revision of the GHS.

Respiratory or skin sensitization : May cause an allergic skin reaction.
No test data available. Irritation properties are evaluated according to the criteria of the third revision of the GHS.

Germ cell mutagenicity : Not classified
(Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified
(Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (single exposure) : May cause respiratory irritation

Specific target organ toxicity (repeated exposure) : Not classified
(Based on available data, the classification criteria are not met)

BlackDiamond® Primer Resin

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Aspiration hazard : Not classified
(Based on available data, the classification criteria are not met)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. DO NOT FLUSH TO SEWER, WATERSHED, OR WATERWAY.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Ecology - waste materials : Avoid release to the environment. DO NOT FLUSH TO SEWER, WATERSHED, OR WATERWAY.

SECTION 14: Transport information

In accordance with DOT
Not regulated for transport

Additional information

Other information : No supplementary information available.

Transport by sea (IMDG)

Transport document description : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (phenol,4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane & Phenol, polymer with formaldehyde, glycidyl ether), 9, III

UN-No. : UN3082

Proper Shipping Name : Environmentally hazardous substance, liquid, n.o.s.

Class : 9 - Class 9 – Environmentally hazardous substance

Packaging group : III

Technical name : phenol,4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane & Phenol, polymer with formaldehyde, glycidyl ether

BlackDiamond® Primer Resin

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Air transport (IATA/ ICAO)

Transport document description	: UN 3082 Environmentally hazardous substance, liquid, n.o.s. (phenol,4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane & Phenol, polymer with formaldehyde, glycidyl ether), 9, III
UN-No.	: UN3082
Proper Shipping Name	: Environmentally hazardous substance, liquid, n.o.s.
Class	: 9 - Class 9 – Environmentally hazardous substance
Packaging group	: III
Technical name	: phenol,4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane Phenol, polymer with formaldehyde, glycidyl ether

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. US State regulations

California Proposition 65 - This product does not contain substances known to the state of California to cause cancer, developmental and/or reproductive harm at low concentration.

SECTION 16: Other information

Indication of changes	: Section 2, Hazards identification Section 3, Composition/information on ingredients
Revision date	: 04/19/2017
Abbreviation	
ANSI	: American Nation Standards Institute
CAS	: Chemical Abstracts Service
CFR	: Code of Federal Regulation
DOT	: Department Of Transportation
GHS	: Globally Harmonized System
IARC	: International Agency for Research on Cancer
IATA	: International Air Transport Association
ICAO	: International Civil Aviation Organization
IMDG	: International Maritime Dangerous Goods
OSHA	: Occupational Safety and Health Administration
PVC	: Polyvinyl Chloride
RCRA	: Resource Conservation and Recovery Act
TSCA	: Toxic Substances Control Act

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product